



Product description

Bus line rectifier for Siedle In-Home bus. For supplying and controlling the bus user audio. For new and existing systems with max. 31 users per line. Up to 15 lines are possible.

AC voltage integrated, for door release and nameplate lighting for example.

Specifications

Operating voltage:	230 V AC, +/-10 %, 50/60 Hz
Operating current:	200 mA
Output voltage:	27.5 V DC, 12 V AC
Output current:	0.5 A DC, 1 A AC
Fusing:	primary fuse 1 T 250 mA L, secondary short circuit proof
Contact type:	2 n.o. contacts 24 V, 2 A
Protection system:	IP 30
Ambient temperature:	0 °C to +40 °C
Horizontal pitch (HP):	9
Dimensions (mm) W x H x D:	162 x 89 x 60

Article information

Article designation	Article description	Colour/Material	KG SAP article no.
BNG 650-0	Bus line rectifier	Black	A 200035140-00

Bus line rectifier
BNG 650-0

Page 2



Accessories

Article designation	Article description	Colour/Material	KG SAP article no.
ZBVG 650-0	Bus supply accessory	Others	A 200035250-00

Spare parts

Article designation	Article description	Colour/Material	KG SAP article no.
BNG 650-..., SNG/VNG 850-...	Fuse holder	Others	E 210005105-00

Bus line rectifier
BNG 650-0

Page 3



Bus line rectifier
BNG 650-0

Page 4



BNG 650-0, BNG 650-1 Bus line rectifier

Product information	477 kB	Download
Declaration of Conformity	1,2 MB	Download
Additional information	109 kB	Download
System manual	11,5 MB	Download